

Outdoor unit:

- 1) IR distance: 3m
- 2) Automatic gain control
- 3) Working temperature: -20°C to +50°C
- 4) Resolution: CMOS camera
- 5) Illumination intensity: 1.5 LUX
- 6) Visual angle: 92° wide-angle
- 7) Size: 119(W) x 162(H) x 56(D)mm
- 8) Power supply (from indoor monitor): DC 12V – 1000mA

7'' Indoor monitor

- 1) Display: 7'' TFT- LCD
- 2) Power supply: Input: AC110-240V, 50-60Hz / Output: DC 15V – 1200mA
- 3) Transmitted method: 2 wires
- 4) Communication duration: 120s +- 10%
- 5) Photos: 120 pictures
- 6) Ring tone: 7 poly-phonic melodies
- 7) Operating distance: Max 100m (based on the cables)
- 8) Working temperature: -10°C to +40°C
- 9) Operating humidity: 10 to 90%
- 10) Size: 190(W) x 137(H) x 22(D)mm
- 11) Image resolution: 800 x 480 dot
- 12) Active area: 154.08(H) x 85.92(V)mm

4'' Indoor monitor

- 1) Display: 4,3'' TFT- LCD
- 2) Power supply: Input: AC110-240V, 50-60Hz / Output: DC 15V – 1200mA
- 3) Transmitted method: 2 wires
- 4) Communication duration: 120s +- 10%
- 5) Ring tone: 7 poly-phonic melodies
- 6) Operating distance: Max 100m (based on the cables)
- 7) Working temperature: -10°C to +40°C
- 8) Operating humidity: 10 to 90%
- 9) Size: 170(W) x 95(H) x 16(D)mm
- 10) Image resolution: 480 x 272 dot
- 11) Active area: 95.04(H) x 53.86(V)mm