



### CPP Chemical Group, S.L

C/ Balsas, 6. 44550 Alcorisa (Teruel).  
Tel. (+34) 978.841.044 / Fax. (+34) 978.841.015

### Administración y Ventas

C/ Mayor, 59 Bajos. 08170  
Montornés de Vallés (Barcelona). Tel. (+34) 935.687.060

## LUXENS LEVEL 1 INTERIOR SATIN

### TECHNICAL SPECIFICATIONS

#### DESCRIPTION

Interior Acrylic satin wall and ceiling paint.

#### RECOMERNDDED USE

Specially designed for interior surfaces made of concrete, precast, plasterboard...

#### GENERAL TECHNICAL PROPERTIES

- Water-based product.
- Satin Finish.
- Good brightness.
- Low odour during coat application and drying.
- Good washability.

#### TECHNICAL DATA

Aspect:	Satin.
Colour:	White.
Solid content:	32.0 ± 0.5 %
Recommended use:	9-11 m <sup>2</sup> /L and coat.
Number of coats:	2
Specific weight:	1.06 – 1.12 g/mL
Dry to the touch:	60 min at 20° C and 60% of relative humidity.
Flammability:	Nonflammable.
VOC's:	max 6.5 g/L (Directive 2004/42 /EC (RD 22/2006) Annex I, subcategory a): 30 g / L max).

#### APLICACION

Instructions for use:	Shake before use.
Method:	Roller or brush.
Dilution:	0 – 5% depending on support or application means.
Thinner and cleaning:	Water.
Time between coats:	Minimum: 3 hours at 20° C Maximum: none.

#### Application conditions:

Prior to painting, check to be sure that the air, surface, and material temperature are below 35°C and above 5°C and relative humidity is under 80%.

The information of this Technical Data Sheet is based on our knowledge and existing laws of the EU and national. The product should not be used for other purposes than the specified in this TDS. It is always your responsibility to take necessary measures to comply with the requirements of the regulations. The information contained in this TDS form should not be considered as a guarantee of its properties.

**CPP Chemical Group, S.L**

C/ Balsas, 6. 44550 Alcorisa (Teruel).  
Tel. (+34) 978.841.044 / Fax. (+34) 978.841.015

**Administración y Ventas**

C/ Mayor, 59 Bajos. 08170  
Montornés de Vallés (Barcelona). Tel. (+34) 935.687.060

---

## SURFACES PREPARATION AND RECOMMENDED PLAN

The support must be completely dry and without any moisture. Eliminate the remains of joints paste, efflorescence, soluble salts, dust, grease, mildew release agents and other pollutants by using any mechanical or manual equipment. Level the imperfections and defects with appropriate products (coating, mastic...).  
In case of new concrete surfaces, do not apply before 28 days from its construction.

*Primer coat:* Apply a water-based under-coat. Let dry 4 hours at 20°C.  
*Finish:* Apply two coats of LUXENS LEVEL 1 INTERIOR SATIN. Apply as uniform as possible.  
Work quickly to avoid roll or brush marks. Let dry 3 hours between coats.

---

## REMARKS

Ensure to respect the indications previously mentioned. Its application over supports in bad conditions, with efflorescence, humidity... do not guarantee the correct adhesion on the surface. Protect those surfaces are not going to be painted (Glass, ceramic, plastics, metals...). The tools should be cleaned with water immediately after its usage. Store the product in a cool and dry place. Avoid direct sun exposure of the package. Do not apply during peak sunlight hours. Do not use salt, chemically contaminated, turbid or excessively chalky water as thinner because it could deteriorate the covering properties. Check the safety precautions described on the package.

---

## SECURITY

Water-based product, does not need any special instructions for its application. The Label contains the corresponding indicators must be taken into account. The national or local legislation requirements must be followed.

Rev: 1/1711

The information of this Technical Data Sheet is based on our knowledge and existing laws of the EU and national. The product should not be used for other purposes than the specified in this TDS. It is always your responsibility to take necessary measures to comply with the requirements of the regulations. The information contained in this TDS form should not be considered as a guarantee of its properties.

Page 2/2