| Trade Mark | Equation | | | | | |
|---|---|----|---------|-----|------|----|
| Model | 100 DV | | | | | |
| Specific energy consumption (SEC), kWh/(m ² .A) | Col | ld | Average | | Warm | |
| | -28,1 | В | -11,7 | Е | -2,3 | F |
| Type of ventilation unit | Unidirectional residential ventilation unit | | | | | |
| Type of drive installed | Single speed | | | | | |
| Type of heat recovery system | None | | | | | |
| Thermal efficiency of heat recovery, % | Non applicable | | | | | |
| Maximum flow rate, m ³ /h | 86 | | | | | |
| Electric power input, W | 15 | | | | | |
| Sound power level, dB(A) | 52 | | | | | |
| Reference flow rate, m ³ /s | 0,017 | | | | | |
| Reference pressure difference, Pa | Not applicable | | | | | |
| Specific power input (SPI), W/(m ³ /h) | 0,174 | | | | | |
| Control typology | Local demand control | | | | | |
| Maximum internal leakage rates, % | Not applicable | | | | | |
| Maximum external leakage rates, % | 2,7% | | | | | |
| Airflow sensitivity at +20 Pa and -20 Pa | 0,15 | | | | | |
| The indoor/outdoor air tightness, m ³ /h | 1 | | | | | |
| Internet address | http://www.erp-equation.com/aerators/ | | | | | |
| The annual electricity consumption (AEC), kWh electricity/a | Col | ld | Aver | age | Wa | rm |
| | 218 | 8 | 21 | .8 | 21 | 18 |
| The annual heating saved (AHS), kWh primary energy/a | Col | ld | Aver | age | Wa | rm |
| | 335 | 55 | 17: | 15 | 77 | 76 |