

Trade Mark	Equation					
Model	100 Ace K					
Specific energy consumption (SEC), kWh/(m <sup>2</sup> .A)	Cold		Average		Warm	
	Type of ventilation unit	-30,1	B	-13,7	E	-4,3
Type of drive installed	Unidirectional residential ventilation unit					
Type of heat recovery system	Single speed					
Thermal efficiency of heat recovery, %	None					
Maximum flow rate, m <sup>3</sup> /h	Non applicable					
Electric power input, W	73					
Sound power level, dB(A)	8					
Reference flow rate, m <sup>3</sup> /s	51					
Reference pressure difference, Pa	0,014					
Specific power input (SPI), W/(m <sup>3</sup> /h)	Not applicable					
Control typology	0,110					
Maximum internal leakage rates, %	Local demand control					
Maximum external leakage rates, %	Not applicable					
Airflow sensitivity at +20 Pa and -20 Pa	2,7%					
The indoor/outdoor air tightness, m <sup>3</sup> /h	0,15					
Internet address	1					
The annual electricity consumption (AEC), kWh electricity/y	<a href="http://www.erp-equation.com/aerators/">http://www.erp-equation.com/aerators/</a>					
	Cold		Average		Warm	
The annual heating saved (AHS), kWh primary energy/y	137		137		137	
	Cold		Average		Warm	
3355		1715		776		