



		<b>Exclusive 320</b>
		 No. 0132-0067-DoP-2016-10 <a href="http://www.home.tarkett.com">http://www.home.tarkett.com</a> <b>Manufactured by:</b> Tarkett GDL SA 2, Op der Sang L-9979 Lentzweiler - Luxembourg EN 14041:2004
	EN ISO 26986	
	EN ISO 10874	

	EN ISO 24346	3,20 mm		EN ISO 717-2	18 dB
	EN ISO 24340	0,30 mm		EN ISO 24343-1	≤ 0,20 mm
	EN ISO 23997	2,300 kg/m <sup>2</sup>		ISO 4918	
		4+3+2m			
	EN ISO 24341	24 m		ISO 11638	

	EN 13893 DIN 51130	μ ≥ 0,30 R10		EN 13501-1	Cfl-S1
	EN 1815	≤ 2 kV		EN ISO 26987	

	EN ISO 23999	≤ 0,40 %		<b>PHthalate FREE</b> Technology *Except recycled content	
	ISO 10456 EN 12524-1	0,05 m <sup>2</sup> /kW		<b>&lt; 100 µg/m<sup>3</sup></b> Better Indoor Air Quality *TVOC AT 28 DAYS	
	EN ISO 105 B02	≥ 6		<b>100 % 18 %</b> Recyclable Recycled content	<b>ÉMISSIONS DANS L'AIR INTÉRIEUR</b> 

#### INSTALACION DE SUELO VINILICO EN ROLLO

- Habitaciones < 12 m<sup>2</sup>  
Instalación libre autoportante



- Habitaciones < 25 m<sup>2</sup>  
Instalación autoportante con cinta de doble cara en perímetro



- Habitaciones > 25 m<sup>2</sup>  
Utilice nuestro spray adhesivo en base agua Tarkospray o adhesivo acrílico tradicional

